Screens » Desking Screens



Collection: Bilby



Screens » Desking Screens





Screens » Desking Screens







MERBAU - TIMBER PET



SPOTTED GUM -TIMBER PET









Screens » Desking Screens

Bilby Desking Screen Extension extends the height of an existing desking screen. It's ideal when you want to add extra privacy or noise absorption.

Description	Bilby panel topper is ideal for when you want to create extra privacy or noise absorption. The extra 12" height is available in 6 widths from 23.5" to 71.5", catering for narrow and wide desking alike. The sustainable PET is available in 24 colors and 4 wood prints so you can match the screen that's already there, or create a visual contrast func., Bilby Desking Screens are easily cleaned with bleach and water.	
Made In	USA	
Dimensions	 23.5" (597mm) w x 12" (305mm) h x 3" (77mm) d 35.5" (902mm) w x 12" (305mm) h x 3" (77mm) d 	
	• 41.5" (1055mm) w x 12" (305mm) h x 3" (77mm) d	
	• 47.5" (1207mm) w x 12" (305mm) h x 3" (77mm) d	
	• 59.5" (1512mm) w x 12" (305mm) h x 3" (77mm) d	
	• 71.5" (1817mm) w x 12" (305mm) h x 3" (77mm) d	
Powder Coat	White ONLY	
PET Colours	24 Colors – Bark, Brick, Cadet, Chambray, Cobalt, Ecru, Fossil, Frost, Grass, Greige, Ivory, Linen, Malachite, Mandarin, Midnight, Ochre, Olive, Pebble, Pewter, Sky, Slate, Smoke, Sunshine, Tar.	
	4 Timber Prints - Eucalyptus, Iron bark, Merbau, Spotted Gum.	
Composition	Density 0.5 lb/ft² 2.4 kg /m²	
Material	• 60% post-consumer recycled PET bottles.	
	 35% pre-consumer recycled content from PET chips 	
	• 5% bio-based Polylactic Acid (PLA)	



Screens » Desking Screens

Fire Ratina	ASTM-E84 - Class A classification
THERAUIN	ACTIVITED TO CIGOSITICATION

AS ISO 9705 - 2003 - Group 1 classification

EN-13501 - B-s2-d0 classification

Warranty 5-year warranty.

Lead Time 4 weeks

Assembly & Delivery Flat pack delivery, minimal assembly required.

See installation instructions for detail.

How to Specify * Select 1 x PET Color

Care Instructions Dab func. with a damp clean cloth and mild solution of liquid detergent and

warm water. Repeat using only clean water, then pat dry with a lint free

cloth.

For difficult stains, use a solution of household bleach (10% bleach / 90%

water).

To remove the bleach, repeat using a clean, water dampened cloth, then

pat dry.

Always test in an inconspicuous area first and if you don't see the expected

results, contact us.

Additional To see how vivid the colors truly are, it's easy to request a sample through

the "Request information" button on this page, or you can ask for one from

your local sales guru.

Inclusions Add-on shell clamp brackets, PET panels



Comments