Screens » Desking Screens



Collection: Murri









IRONBARK - TIMBER PET



MERBAU - TIMBER PET



SPOTTED GUM -TIMBER PET

Screens » Desking Screens



Murri Desking Screen is a contemporary screen with noise and germ blocking acrylic side panels that's perfect for height adjustable desks and tables.

Description

Balances front on privacy with adjacent light, a contemporary desking screen with the addition of germ and noise blocking acrylic side panels.

Its modern design and use of shell clamps mean it works with almost any worksurface or height adjustable table. The 36" high screen is available in 7 widths from 47"-72", 24 PET colors and 4 wood prints.

func., Murri Desking Screens are easily cleaned with bleach and water.

Made In

USA



Dimensions	• 47" (1200mm) w x 36" (915mm) h x 24" (616mm) d
	• 48" (1220mm) w x 36" (915mm) h x 24" (616mm) d
	• 55" (1400mm) w x 36" (915mm) h x 24" (616mm) d
	• 60" (1524mm) w x 36" (915mm) h x 24" (616mm) d
	• 63" (1600mm) w x 36" (915mm) h x 24" (616mm) d
	• 71" (1800mm) w x 36" (915mm) h x 24" (616mm) d
	• 72" (1829mm) w x 36" (915mm) h x 24" (616mm) d
Powder Coat	White ONLY
PET Colours	24 Colors – Bark, Brick, Cadet, Chambray, Cobalt, Ecru, Fossil, Frost, Grass, Greige, Ivory, Linen, Malachite, Mandarin, Midnight, Ochre, Olive, Pebble, Pewter, Sky, Slate, Smoke, Sunshine, Tar.
	4 Timber Prints - Eucalyptus, Iron bark, Merbau, Spotted Gum.
Acrylic	• Clear
	• Frosted
Composition	Density 0.5 lb/ft² 2.4 kg /m²
Material	60% post-consumer recycled PET bottles.
	 35% pre-consumer recycled content from PET chips
	• 5% bio-based Polylactic Acid (PLA)
Fire Rating	ASTM-E84 – Class A classification AS ISO 9705 – 2003 – Group 1 classification EN-13501 – B-s2-d0 classification
Warranty	5-year warranty.



Lead Time	4 weeks
Assembly & Delivery	Flat pack delivery, minimal assembly required. See installation instructions for detail.
How to Specify	 Select 1 x PET Color White Powder Coat Finish Only Select 1 x Wood Finish Refer Product Specification Guide
Care Instructions	Dab func. with a damp clean cloth and mild solution of liquid detergent and warm water. Repeat using only clean water, then pat dry with a lint free cloth. For difficult stains, use a solution of household bleach (10% bleach / 90% water). To remove the bleach, repeat using a clean, water dampened cloth, then pat dry. Always test in an inconspicuous area first and if you don't see the expected results, contact us.
Additional Comments	To see how vivid the colors truly are, it's easy to request a sample through the "Request information" button on this page, or you can ask for one from your local sales guru.
Inclusions	Desk Clamp Brackets, PET panels, Acrylic panels, Fixing Hardware

