Screens » Floor Screens



Collection: Alinta









MERBAU - TIMBER PET



IRONBARK - TIMBER
PET



SPOTTED GUM -TIMBER PET

Screens » Floor Screens



Alinta Floor Screen is lightweight and easy to move. The horizontal spacing between the panels is designed to balance privacy, acoustics, and light.

Absorbs Noise	Easy Install	• Easy Clean
ADSOLDS MOISE	• Eusy Ilistuli	Eusy Cleur

Bleach Cleanable
 Acoustic

Description

The Alinta Floor Screen turns almost any open space into a workspace. It's V-fold gives a strong, angular aesthetic, while its lightweight construction makes it easy to move and create spaces wherever you need them. The design's horizontal spacing between the PET panels balances privacy, acoustics, and light.

This is highly configurable screen, comes in 61" and 72" heights and 48", 72" and 96" widths. All sizes come in 24 PET colors, 4 wood prints and the choice of blonde, dark, white, or black wood supports.

func., Alinta Floor Screens are easily cleaned with bleach and water.

Made In USA



Dimensions	 48" (1220mm) w x 61" (1550mm) h x 15" (377mm) d 48" (1220mm) w x 72" (1829mm) h x 15" (377mm) d 72" (1829mm) w x 61" (1550mm) h x 15" (377mm) d 72" (1829mm) w x 72" (1829mm) h x 15" (377mm) d 96" (2439mm) w x 61" (1550mm) h x 15" (377mm) d 96" (2439mm) w x 72" (1829mm) h x 15" (377mm) d
PET Colours	 24 Colors – Bark, Brick, Cadet, Chambray, Cobalt, Ecru, Fossil, Frost, Grass, Greige, Ivory, Linen, Malachite, Mandarin, Midnight, Ochre, Olive, Pebble, Pewter, Sky, Slate, Smoke, Sunshine, Tar. 4 Timber Prints – Eucalyptus, Iron bark, Merbau, Spotted Gum.
Wood	BlondeDarkWhiteBlack
Composition	Density 0.5 lb/ft² 2.4 kg /m²
Material	 60% post-consumer recycled PET bottles. 35% pre-consumer recycled content from PET chips 5% bio-based Polylactic Acid (PLA)
Fire Rating	ASTM-E84 – Class A classification AS ISO 9705 – 2003 – Group 1 classification EN-13501 – B-s2-d0 classification
Warranty	5-year warranty.



Lead Time	4 weeks	
Assembly & Delivery	Flat pack delivery, minimal assembly required. See installation instructions for detail.	
How to Specify	 Select 1 x PET Color Select 1 x Wood Finish Refer Product Specification Guide 	
Care Instructions	Dab func. with a damp clean cloth and mild solution of liquid detergent and warm water. Repeat using only clean water, then pat dry with a lint free cloth. For difficult stains, use a solution of household bleach (10% bleach / 90% water). To remove the bleach, repeat using a clean, water dampened cloth, then pat dry. Always test in an inconspicuous area first and if you don't see the expected results, contact us.	
Additional Comments	To see how vivid the colors truly are, it's easy to request a sample through the "Request information" button on this page, or you can ask for one from your local sales guru.	
Inclusions	Wood Supports, PET Panels	

