

KAYA SLIDING SCREEN

Screens » Suspended Screens



Collection: **Kaya**

KAYA SLIDING SCREEN

Screens » Suspended Screens



BARK - PET



BRICK - PET



CADET - PET



CHAMBRAY - PET



COBALT - PET



ECRU - PET



FOSSIL - PET



FROST - PET



GRASS - PET



GREIGE - PET



IVORY - PET



LINEN - PET



MALACHITE - PET



MANDARIN - PET



MIDNIGHT - PET



OCHRE - PET



OLIVE - PET



PEBBLE - PET



PEWTER - PET



SKY - PET



SLATE - PET



SMOKE - PET



SUNSHINE - PET



TAR - PET




EUCALYPTUS - TIMBER
PET

KAYA SLIDING SCREEN

Screens » Suspended Screens



IRONBARK - TIMBER
PET



MERBAU - TIMBER PET



SPOTTED GUM -
TIMBER PET

KAYA SLIDING SCREEN

Screens » Suspended Screens



Kaya Sliding Screen hangs on horizontal mounting tracks attached to the ceiling. It means smooth, easy movement and excellent space creation.

- Absorbs Noise
- Bleach Cleanable
- Easy Install
- Acoustic
- Easy Clean

Description

The Kaya Sliding Screen hangs on horizontal mounting tracks for smooth, easy movement.

The Grille, Lattice or Plain designs are complemented with optional acrylic for privacy or a writeable surface for those creative moments. Available in 24 PET colors or 4 wood prints, the option of adding multiple screens makes it's ideal for expandable acoustic management in small or large spaces.

func., Kaya Sliding Screens are easily cleaned with bleach and water.

Made In

USA

Dimensions

47.5" (1207mm) w x 108" (2744mm) h x 3" (55mm) d

KAYA SLIDING SCREEN

Screens » Suspended Screens

PET Colours **24 Colors** – Bark, Brick, Cadet, Chambray, Cobalt, Ecu, Fossil, Frost, Grass, Greige, Ivory, Linen, Malachite, Mandarin, Midnight, Ochre, Olive, Pebble, Pewter, Sky, Slate, Smoke, Sunshine, Tar.

4 Timber Prints – Eucalyptus, Iron bark, Merbau, Spotted Gum.

Composition Density 0.5 lb/ft² 2.4 kg /m²

- Material**
- 60% post-consumer recycled PET bottles.
 - 35% pre-consumer recycled content from PET chips
 - 5% bio-based Polylactic Acid (PLA)
-

Fire Rating ASTM-E84 – Class A classification
AS ISO 9705 – 2003 – Group 1 classification
EN-13501 – B-s2-d0 classification

Warranty 5-year warranty.

Lead Time 4 weeks

Assembly & Delivery Flat pack delivery, minimal assembly required. See installation instructions for detail.

KAYA SLIDING SCREEN

Screens » Suspended Screens

How to Specify

- Select 1 x PET Color
 - Powder Coat Finish WHITE ONLY
1. Select Design
 - Grille
 - Lattice
 - Plain Design
 2. Select Acrylic - if Option selected
 - Clear
 - Frosted
 3. Select Writeable Surface - if option selected
 - Refer to Product Specification Guide
-

Care Instructions

Dab func. with a damp clean cloth and mild solution of liquid detergent and warm water. Repeat using only clean water, then pat dry with a lint free cloth.

For difficult stains, use a solution of household bleach (10% bleach / 90% water).

To remove the bleach, repeat using a clean, water dampened cloth, then pat dry.

Always test in an inconspicuous area first and if you don't see the expected results, contact us.

Additional Comments

To see how vivid the colors truly are, it's easy to request a sample through the "Request information" button on this page, or you can ask for one from your local sales guru.

Inclusions

PET panel with roller hardware fitted.
